

**SAFETY DATA SHEET****Floorwise F599**

According to Regulation (EC) No 1907/2006, Annex II

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Product name** Floorwise F599

**Container size** 500ml

**REACH registration notes** All chemicals used in this product have been registered under REACH where required.

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Adhesive.

**Uses advised against** Flexible PVC due to the risk of plasticiser migration.

**1.3. Details of the supplier of the safety data sheet**

**Supplier** Floorwise Group Ltd  
Floorwise House  
22 High Street  
Kegworth  
Derby  
DE74 2DA  
Tel: 01509 673 974  
Fax: 01509 674 841

**1.4. Emergency telephone number**

**Emergency telephone** Floorwise: +44 (0) 1509 673 974 (Mon-Fri 09:00-17:00)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification (EC 1272/2008)**

**Physical hazards** Aerosol 1 - H222, H229

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Carc. 2 - H351 STOT SE 3 - H336

**Environmental hazards** Aquatic Chronic 3 - H412

**2.2. Label elements****Pictogram****Signal word**

Danger

**Hazard statements**

H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H412 Harmful to aquatic life with long lasting effects.

## Floorwise F599

<b>Precautionary statements</b>	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
<b>Supplemental label information</b>	Please refer to Safety Data Sheet.
<b>Contains</b>	DICHLOROMETHANE, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
<b>Supplementary precautionary statements</b>	<p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P273 Avoid release to the environment.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P405 Store locked up.</p>

### 2.3. Other hazards

Dichloromethane is converted to carbon monoxide in the body, which reduces the oxygen carrying capacity of the blood. In use may form flammable/explosive vapour-air mixture. This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>DICHLOROMETHANE</b>			<b>30-60%</b>
CAS number: 75-09-2	EC number: 200-838-9	REACH registration number: 01-2119480404-41	
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Carc. 2 - H351 STOT SE 3 - H336			
<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b>			<b>30-60%</b>
CAS number: 68476-85-7	EC number: 270-704-2		
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas, Liquefied - H280			

## Floorwise F599

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			1-5%
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35-XXXX	
<b>Classification</b>			
Flam. Liq. 2 - H225			
Skin Irrit. 2 - H315			
STOT SE 3 - H336			
Asp. Tox. 1 - H304			
Aquatic Chronic 2 - H411			

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Composition comments** CAS 68476-85-7 Petroleum gases - as the substance contains less than 0.1%w/w 1,3-butadiene the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air at once.
<b>Inhalation</b>	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water. DO NOT induce vomiting. Get medical attention immediately.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Use hand wash which is specific to the removal of adhesive. Do not use solvents to clean skin.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. If adhesive bonding occurs, do not force eyelids apart.
<b>Protection of first aiders</b>	No specific requirements are anticipated under normal conditions of use.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
<b>Inhalation</b>	Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
<b>Ingestion</b>	There may be soreness and redness of the mouth and throat.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin. Contains components which may penetrate the skin. Product has a defatting effect on skin.
<b>Eye contact</b>	Irritation of eyes and mucous membranes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	The following symptoms may occur: Nausea, headache, dizziness, coughing and breathing difficulty.
<b>Specific treatments</b>	If adhesive bonding occurs, do not force eyelids apart.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

## Floorwise F599

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

**Hazardous combustion products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Phosgene (COCl<sub>2</sub>). Hydrogen chloride (HCl).

### 5.3. Advice for firefighters

**Protective actions during firefighting** Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes. If ventilation is inadequate, suitable respiratory protection must be worn.

**For non-emergency personnel** For the greatest protection, clothing should include anti-static overalls, boots and gloves.

**For emergency responders** For the greatest protection, clothing should include anti-static overalls, boots and gloves.

### 6.2. Environmental precautions

**Environmental precautions** Contain the spillage using bunding. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Approach the spillage from upwind. Take precautionary measures against static discharge. Use only non-sparking tools.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Wear appropriate personal protective equipment (see Section 8) Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using the product.

## Floorwise F599

### Advice on general occupational hygiene

Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas. Wash after use and before eating, smoking and using the toilet. Do not smoke in work area. Clean equipment and the work area every day.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Do not use containers made of the following materials: Aluminium. Pressurised container: may burst if heated Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Do not pierce or burn, even after use.

#### Storage class

Extremely Flammable Aerosol

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

#### Usage description

Adhesive. Store in a flammable storage cupboard according to national regulations.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### DICHLOROMETHANE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 350 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 1060 mg/m<sup>3</sup>(Sk)

##### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit

#### DICHLOROMETHANE (CAS: 75-09-2)

##### DNEL

Industry - Inhalation; Long term : 353 mg/m<sup>3</sup>  
 Industry - Dermal; Long term : 4750 mg/kg/day  
 Industry - Inhalation; Short term : 706 mg/m<sup>3</sup>  
 Consumer - Inhalation; Long term : 88.3 mg/m<sup>3</sup>  
 Consumer - Oral; Short term : 0.06 mg/kg/day  
 Consumer - Inhalation; Short term : 353 mg/m<sup>3</sup>  
 Consumer - Dermal; Short term : 2395 mg/kg/day

##### PNEC

- Fresh water; 0.54 mg/l  
 - Marine water; 0.194 mg/l  
 - Sediment (Freshwater); 1.61 mg/kg  
 - STP; 26 mg/l  
 - Soil; 0.583 mg/kg  
 - Intermittent release; 0.27 mg/l

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

##### DNEL

Consumer - Oral; Long term systemic effects: 699 mg/kg/day  
 Workers - Oral; Long term systemic effects: 2035 mg/kg/day  
 Consumer - Dermal; Long term systemic effects: 699 mg/kg/day  
 Workers - Dermal; Long term systemic effects: 773 mg/kg/day  
 Consumer - Inhalation; Long term systemic effects: 608 mg/m<sup>3</sup>

## Floorwise F599

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

#### Personal protection

Wear protective work clothing.

#### Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

#### Hand protection

Viton rubber (fluoro rubber). The selected gloves should have a breakthrough time of at least 2 hours. Minimum thickness: 0.7mm

#### Other skin and body protection

Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure to the skin.

#### Hygiene measures

Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash hands at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. For short term use an AX filter is recommended.

#### Thermal hazards

Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

#### Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Amber.
Odour	Chlorinated hydrocarbons.
Odour threshold	Not available.
pH	Not available.
Melting point	Not applicable.
Initial boiling point and range	40°C @ 760 mm Hg Boiling point of dichloromethane.
Flash point	A flash point method is not available but the major hazardous component, the Propellant has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower.
Evaporation rate	27.5 For dichloromethane (n Butyl Acetate =1)

## Floorwise F599

Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Other flammability	Not available.
Vapour pressure	4-6 bar @ 20°C
Vapour density	Not available.
Relative density	~1.18 @ 20°C Density of liquid base.
Bulk density	Not applicable.
Solubility(ies)	Insoluble in water.
Partition coefficient	log Pow: 1.25 Dichloromethane
Auto-ignition temperature	Not available.
Decomposition Temperature	Data lacking.
Viscosity	50-150 mPa s @ 20°C Viscosity of liquid base.
Explosive properties	In use may form flammable/explosive vapour-air mixture.
Explosive under the influence of a flame	Yes
Oxidising properties	Does not meet the criteria for classification as oxidising.
Comments	A flash point method is not available but the major hazardous component, the Propellant has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower.

### 9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 612 g/l.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	Vapours may form explosive mixtures with air.
------------	---

### 10.2. Chemical stability

Stability	Highly volatile.
-----------	------------------

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise. In use may form flammable/explosive vapour-air mixture.
------------------------------------	--

### 10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Avoid the accumulation of vapours in low or confined areas.
---------------------	--

### 10.5. Incompatible materials

Materials to avoid	Aluminium Flexible PVC due to the risk of plasticiser migration.
--------------------	--

### 10.6. Hazardous decomposition products

## Floorwise F599

**Hazardous decomposition products** Toxic gases/vapours/fumes of: Hydrogen chloride (HCl). Phosgene (COCl<sub>2</sub>). Carbon monoxide (CO).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

<b>General information</b>	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
<b>Inhalation</b>	High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations may cause anaesthetic effects and asphyxiation. There may be irritation of the throat with a feeling of tightness in the chest.
<b>Ingestion</b>	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause nausea, headache, dizziness and intoxication.
<b>Skin contact</b>	Prolonged contact may result in skin irritation. Contains a substance that maybe harmful through skin absorption. Absorption of organic solvents through the skin can cause the same effects as inhalation
<b>Eye contact</b>	Irritating to eyes.
<b>Acute and chronic health hazards</b>	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
<b>Route of entry</b>	Inhalation Skin absorption Ingestion
<b>Target organs</b>	Central nervous system Respiratory system, lungs Liver
<b>Medical symptoms</b>	Narcotic effect. Drowsiness. Dizziness.

#### Toxicological information on ingredients.

#### DICHLOROMETHANE

##### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> 2,000.1 mg/kg)

Species Rat

ATE oral (mg/kg) 2,000.1

##### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> 2,000.1 mg/kg)

Species Rat

ATE dermal (mg/kg) 2,000.1

##### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 86.0

Species Rat

ATE inhalation (vapours mg/l) 86.0

##### Skin corrosion/irritation



## Floorwise F599

<b>Skin corrosion/irritation</b>	Irritating to skin.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	Slightly irritating.
<b><u>Respiratory sensitisation</u></b>	
<b>Respiratory sensitisation</b>	There is evidence that the product can cause respiratory hypersensitivity.
<b><u>Skin sensitisation</u></b>	
<b>Skin sensitisation</b>	Not sensitising.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Genome mutation: Positive.
<b>Genotoxicity - in vivo</b>	Chromosome aberration: Negative.
<b><u>General information</u></b>	
	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Known or suspected carcinogen for humans.
<b>Inhalation</b>	Harmful by inhalation. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Irritating to respiratory system. Unconsciousness. High concentrations may be fatal. Vapours in high concentrations are anaesthetic.
<b>Ingestion</b>	May cause nausea, headache, dizziness and intoxication.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin. Product has a defatting effect on skin. May cause skin irritation/eczema.
<b>Eye contact</b>	Irritating to eyes.
<b>Acute and chronic health hazards</b>	Contains a substance which may be potentially carcinogenic.
<b>Route of entry</b>	Inhalation. Skin absorption. Ingestion. Skin and/or eye contact
<b>Target organs</b>	Central nervous system. Liver. Kidneys. Skin. Respiratory system, lungs. Heart and cardiovascular system Eyes
<b>Medical symptoms</b>	Dilated pupils. Severe skin irritation. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Hypotension (low blood pressure). Unconsciousness, possibly death.
<b>Medical considerations</b>	Skin disorders and allergies. Liver and/or kidney damage. Convulsive disorders, CNS problems. History of smoking.
<b><u>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</u></b>	
<b><u>Acute toxicity - inhalation</u></b>	
<b>Notes (inhalation LC<sub>50</sub>)</b>	>20 mg/l, Inhalation, Rat
<b><u>Skin corrosion/irritation</u></b>	
<b>Skin corrosion/irritation</b>	Not irritating.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	This substance has no evidence of mutagenic properties.

## Floorwise F599

### Carcinogenicity

**Carcinogenicity** No evidence of carcinogenicity in animal studies.

### Reproductive toxicity

**Reproductive toxicity - fertility** No evidence of reproductive toxicity in animal studies.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Gas or vapour is harmful on prolonged exposure or in high concentrations. High concentrations may be fatal.

### Aspiration hazard

**Aspiration hazard** Not anticipated to present an aspiration hazard, based on chemical structure.

**Inhalation** May cause respiratory system irritation.

**Skin contact** Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

**Route of entry** Inhalation Skin and/or eye contact

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** LD<sub>50</sub> >5000 mg/kg, Oral, Rat

### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** LD<sub>50</sub> >2000 mg/kg, Dermal, Rabbit

### Skin corrosion/irritation

**Skin corrosion/irritation** Skin irritation.

### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

## Floorwise F599

### Aspiration hazard

#### Aspiration hazard

May be fatal if swallowed and enters airways.

## SECTION 12: Ecological Information

### Ecotoxicity

The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

### Ecological information on ingredients.

#### DICHLOROMETHANE

#### Ecotoxicity

The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

### 12.1. Toxicity

#### Toxicity

Not regarded as dangerous for the environment Not considered toxic to fish.

### Ecological information on ingredients.

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

#### Toxicity

Not regarded as dangerous for the environment.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Acute toxicity - fish

LC<sub>50</sub>, : 1-10 mg/l, Fish  
NOEC, : 1-10 mg/l, Fish

#### Acute toxicity - microorganisms

LC<sub>50</sub>, : 1-10 mg/l, Activated sludge  
NOEC, : 0.1-1 mg/l, Activated sludge

### 12.2. Persistence and degradability

**Persistence and degradability** No data available. There are no data on the degradability of this product.

### Ecological information on ingredients.

#### DICHLOROMETHANE

#### Persistence and degradability

Biodegradable

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

#### Persistence and degradability

The product is degraded completely by photochemical oxidation.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

#### Bioaccumulative potential

Dichloromethane has low bioaccumulative potential

#### Partition coefficient

log Pow: 1.25 Dichloromethane

### Ecological information on ingredients.

## Floorwise F599

### DICHLOROMETHANE

**Bioaccumulative potential** The product contains potentially bioaccumulating substances.

**Partition coefficient** log Pow: 1.25

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

**Bioaccumulative potential** Bioaccumulation is unlikely.

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Bioaccumulative potential** Not available.

#### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

#### Ecological information on ingredients.

### DICHLOROMETHANE

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water.

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** Not determined

#### Ecological information on ingredients.

### DICHLOROMETHANE

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

**Ozone depletion potential**

**Global warming potential (GWP)**

#### Ecological information on ingredients.

### DICHLOROMETHANE

**Other adverse effects** None known.

## Floorwise F599

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Other adverse effects

The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>General information</b>	Ensure containers are empty before discarding (explosion risk). Must not be disposed of together with household waste.
<b>Disposal methods</b>	Do not puncture or incinerate, even when empty. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
<b>Waste class</b>	Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 04 (No hazardous residues). Empty Aerosol: 15 01 10 (Containing hazardous residues).

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

#### Transport labels



#### 14.4. Packing group

Not applicable.

## Floorwise F599

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	Health and Safety at Work etc. Act 1974 (as amended). The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
<b>EU legislation</b>	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
<b>Guidance</b>	Workplace Exposure Limits EH40.
<b>Authorisations (Title VII Regulation 1907/2006)</b>	No specific authorisations are known for this product.
<b>Restrictions (Title VIII Regulation 1907/2006)</b>	No specific restrictions on use are known for this product.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

## SECTION 16: Other information

<b>Classification procedures according to Regulation (EC) 1272/2008</b>	Aerosol 1 - H222, H229: Weight of evidence. Carc. 2 - H351: Calculation method. Skin Irrit. 2 - H315: Calculation method. STOT SE 3 - H336: Calculation method. Aquatic Chronic 3 - H412: Calculation method.
<b>Issued by</b>	Technical Department
<b>Revision date</b>	21/01/2016
<b>Revision</b>	8
<b>Supersedes date</b>	05/11/2015
<b>SDS number</b>	20654

## Floorwise F599

### Hazard statements in full

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H229 Pressurised container: may burst if heated  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.