

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019Revision date 07-Jul-2021
Revision Number 1.01**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier****Product Name** BOSTIK STIX A550 POWER ELASTIC
Pure substance/mixture Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Adhesive.
Uses advised against None known**1.3. Details of the supplier of the safety data sheet****Company Name**
Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****United Kingdom** +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

Skin sensitisation Category 1 - (H317)**2.2. Label elements**

Contains 2-methyl-2H-isothiazol-3-one [MIT]; 1,2-benzisothiazol-3(2H)-one [BIT]; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]

**Signal word**

Warning

Hazard statements

H317 - May cause an allergic skin reaction.

Precautionary Statements - EU (§28, 1272/2008)P102 - Keep out of reach of children
P261 - Avoid breathing vapours/spray
P280 - Wear protective gloves
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Zinc oxide	215-222-5	1314-13-2	0.1 - <1	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (M Factor Acute = 1) (M Factor Chronic = 1)		01-2119463881-32-XXXX
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9	2634-33-5	0.01 - <0.05	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411) M Factor Acute =1	Skin Sens. 1 :: C>=0.05%	01-2120761540-60-XXXX
2-methyl-2H-isothiazol-3-one [MIT]	220-239-6	2682-20-4	0.0015 - <0.01	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic	Skin Sens. 1 :: C>=0.0015%	01-2120764690-50-xxxx

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

				1 (H410) M Factor Acute =10 M Factor Chronic = 1		
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute = 100 M Factor Chronic = 100	Eye Dam. 1 :: C>=0.6% Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691-48-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Do NOT induce vomiting. If swallowed, rinse mouth with water (only if the person is conscious). Call a doctor or poison control centre immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supercedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Use personal protection equipment.

General hygiene considerations When using do not eat, drink or smoke. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing. Keep away from food, drink and animal feedingstuffs.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

7.3. Specific end use(s)

Specific use(s)

Adhesive.

Identified uses

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Quartz 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Sodium hydroxide 1310-73-2	-	STEL: 2 mg/m ³
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Zinc oxide (1314-13-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	5 mg/m ³	
worker Long term Local health effects	Inhalation	0.5 mg/m ³	
worker Long term Systemic health effects	Dermal	83 mg/kg bw/d	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m ³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)

Zinc oxide (1314-13-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Inhalation	2.5 mg/m ³	

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

Systemic health effects			
Consumer Long term Systemic health effects	Dermal	83 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.83 mg/kg bw/d	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m ³	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Zinc oxide (1314-13-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0206 mg/l
Marine water	0.0061 mg/l
Freshwater sediment	235.6 mg/kg dry weight
Marine sediment	113 mg/kg dry weight
Soil	106.8 mg/kg dry weight
Microorganisms in sewage treatment	0.1 mg/l

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Use with local exhaust ventilation in the case of spray application.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection

Wear suitable gloves. Recommended Use: Nitrile rubber. Butyl rubber. Neoprene™. Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Gloves must conform to standard EN 374

Skin and body protection

Suitable protective clothing.

Respiratory protection

During spraying wear suitable respiratory equipment. Wear a respirator conforming to EN 140 with Type A/P2 filter or better.

Recommended filter type:

Organic gases and vapours filter conforming to EN 14387. Brown. White.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	No information available
Colour	White Beige
Odour	Slight Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	6.5 - 8.5	
pH (as aqueous solution)	No data available	
Melting point / freezing point	0 °C	
Initial boiling point and boiling range	100 °C	
Flash point	approx No data available	
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	1.3	
Water solubility	partially soluble	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	
Density	ca. 1.3 g/cm ³

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Stable.
------------	---------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supercedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Do not freeze.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.
Eye contact Based on available data, the classification criteria are not met.
Skin contact May cause sensitisation by skin contact.
Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms None known.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 13,002.60 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Zinc oxide 1314-13-2	>5000 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LC50 (4h) >5.7 mg/l
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	
2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4	LD50 =285 mg/Kg (Rattus)	LD50 >242 mg/Kg (Rattus)	=0.11 mg/L (Rattus) 4 h
reaction mass of 5-chloro-2-methyl-2H-isothiazol 1-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	=53 mg/kg (Rattus)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Zinc oxide 1314-13-2	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L (Danio rerio)	-	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)	1	1
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	
2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4	EC50 (72hr) 0.157 mg/l (Pseudokirchner)	EC50 (96hr) 5.71 mg/l (Oncorhynchus)	-	EC50 (48hr) 1.68 mg/l (Daphnia)	10	1

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

	iella subcapitata) (OECD 201)	mykiss) OECD 203		(OECD 202)		
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information

Zinc oxide (1314-13-2)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

2-methyl-2H-isothiazol-3-one [MIT] (2682-20-4)

Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and Anaerobic Transformation in Aquatic Sediment Systems		Half-life	1.28-2.1 days
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		biodegradation Half-life	Readily biodegradable 4.1 days

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	0.7	6.95
2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4	-0.32	3.16
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	-	3.16

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Zinc oxide 1314-13-2	The substance is not PBT / vPvB PBT assessment does not apply
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

2634-33-5	
2-methyl-2H-isothiazol-3-one [MIT] 2682-20-4	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

SAFETY DATA SHEET

BOSTIK STIX A550 POWER ELASTIC
Supersedes Date: 19-Sep-2019

Revision date 07-Jul-2021
Revision Number 1.01

H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H411 - Toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 07-Jul-2021

Indication of changes

Revision note SDS sections updated: 5, 8, 15.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet